

GLOBE VALVE

STRAIGHT | CAST IRON | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7305 - STOP TYPE
JIS F7353 - SDNR TYPE
CONNECTION : JIS 5K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750201	751101	50	210	130	105	4	15	14.7
750202	751102	65	250	155	130	4	15	21.3
750203	751103	80	280	180	145	4	19	27.7
750204	751104	100	340	200	165	8	19	40.8
750205	751105	125	410	235	200	8	19	57.6
750206	751106	150	480	265	230	8	19	80.3
750207	751107	200	570	320	280	8	23	139
750208	751108	250	740	385	345	12	23	246
750209	751109	300	840	430	390	12	23	377
750210	751110	350	940	480	435	12	25	462
750211	751111	400	1050	540	495	16	25	647



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com