

GLOBE VALVE

STRAIGHT | CAST STEEL | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7311 - STOP TYPE
JIS F7311C - SDNR TYPE
CONNECTION : JIS 5K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750301	750310	50	210	130	105	4	15	14.7
750302	750311	65	250	155	130	4	15	21.3
750303	750312	80	280	180	145	4	19	27.7
750304	750313	100	340	200	165	8	19	40.8
750305	750314	125	410	235	200	8	19	57.6
750306	750315	150	480	265	230	8	19	80.3
750307	750316	200	570	320	280	8	23	139
750308	750401-C	250	740	385	345	12	23	246
750309	750402-C	300	840	430	390	12	23	377
750403	750403-C	350	940	480	435	12	25	462
750404	750404-C	400	1050	540	495	16	25	647



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com