

GLOBE VALVE

STRAIGHT | CAST STEEL | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7319 - STOP TYPE
JIS F7471 - SDNR TYPE
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750411	751201	50	220	155	120	4	19	17.9
750412	751202	65	270	175	140	4	19	26
750413	751203	80	300	185	150	8	19	29.8
750414	751204	100	350	210	175	8	19	44.7
750415	751205	125	420	250	210	8	23	70.3
750416	751206	150	490	280	240	8	23	96.4
750417	751207	200	570	330	290	12	23	159
750418	751208	250	740	400	355	12	25	257
750419	751209	300	840	445	400	16	25	378



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com