

GLOBE VALVE

STRAIGHT | CAST IRON | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7307 - STOP TYPE
JIS F7377 - SDNR TYPE
CONNECTION : JIS 10K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750231	751131	50	220	155	120	4	19	17.9
750232	751132	65	270	175	140	4	19	26
750233	751133	80	300	185	150	8	19	29.8
750234	751134	100	350	210	175	8	19	44.7
750235	751135	125	420	250	210	8	23	70.3
750236	751136	150	490	280	240	8	23	96.4
750237	751137	200	570	330	290	12	23	159
750238	751138	250	740	400	355	12	25	257
750239	751139	300	840	445	400	16	25	378



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com