

GLOBE VALVE STRAIGHT | CAST STEEL | JIS 20K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7313 - STOP TYPE
JIS F7473 - SDNR TYPE
CONNECTION : JIS 20K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750431	751231	32	190	135	100	4	19	14.4
750432	751232	40	200	140	105	4	19	16
750433	751233	50	230	155	120	8	19	21.6
750434	751234	65	270	175	140	8	19	30.4
750435	751235	80	300	200	160	8	23	43.5
750436	751236	100	350	225	185	8	23	62.3
750437	751237	125	430	270	225	8	25	95.7
750438	751238	150	500	305	260	12	25	133.3
750439	751239	200	560	350	305	12	25	296.1
750440	751240	250	660	430	380	12	27	339.1



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com