

GLOBE VALVE

STRAIGHT | CAST IRON | JIS 16K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7309 - STOP TYPE
JIS F7375 - SDNR TYPE
CONNECTION : JIS 16K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750261	751151	50	220	155	120	8	19	19.6
750262	751152	65	270	175	140	8	19	28.3
750263	751153	80	300	200	160	8	23	40.4
750264	751154	100	350	225	185	8	23	56.9
750265	751155	125	430	270	225	8	25	89.5
750266	751156	150	500	305	260	12	25	123
750267	751157	200	570	350	305	12	25	188



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com