

GLOBE VALVE ANGLE | CAST STEEL | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7320 - STOP TYPE
JIS F7472 - SDNR TYPE
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750421	751216	50	120	155	120	4	19	18.2
750422	751217	65	130	175	140	4	19	25.4
750423	751218	80	140	185	150	8	19	27.4
750424	751219	100	160	210	175	8	19	40.6
750425	751220	125	180	250	210	8	23	69.9
750426	751221	150	205	280	240	8	23	81
750427	751222	200	230	330	290	12	23	125
750428	751223	250	290	400	355	12	25	211
750429	751224	300	320	445	400	16	25	293



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com