

GLOBE VALVE ANGLE | CAST IRON | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7306 - STOP TYPE
JIS F7354 - SDNR TYPE
CONNECTION : JIS 5K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750216	751116	50	100	130	105	4	15	13
750217	751117	65	115	155	130	4	15	18.2
750218	751118	80	130	180	145	4	19	23.3
750219	751119	100	150	200	165	8	19	33.5
750220	751120	125	170	235	200	8	19	46.5
750221	751121	150	190	265	230	8	19	64
750222	751122	200	220	320	280	8	23	104
750223	751123	250	275	385	345	12	23	175
750224	751124	300	310	430	390	12	23	243
750225	751125	350	360	480	435	12	25	336
750226	751126	400	395	540	495	16	25	455



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com