

GLOBE VALVE

ANGLE | CAST STEEL | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7312 - STOP TYPE
JIS F7312C - SDNR TYPE
CONNECTION : JIS 5K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750320	750330	50	100	130	105	4	15	13
750321	750331	65	115	155	130	4	15	18.2
750322	750332	80	130	180	145	4	19	23.3
750323	750333	100	150	200	165	8	19	33.5
750324	750334	125	170	235	200	8	19	46.5
750325	750335	150	190	265	230	8	19	64
750326	750336	200	220	320	280	8	23	104
750406	750406-C	250	275	385	345	12	23	175
750407	750407-C	300	310	430	390	12	23	243
750408	750408-C	350	360	480	435	12	25	336
750409	750409-C	400	395	540	495	16	25	455



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com