

GLOBE VALVE ANGLE | CAST IRON | JIS 16K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7310 - STOP TYPE
JIS F7378 - SDNR TYPE
CONNECTION : JIS 16K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750271	751161	50	120	155	120	8	19	18
750272	751162	65	130	175	140	8	19	25
750273	751163	80	150	200	160	8	23	35.7
750274	751164	100	170	225	185	8	23	49.2
750275	751165	125	200	270	225	8	25	76.1
750276	751166	150	225	305	260	12	25	103
750277	751167	200	250	350	305	12	25	155



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com