

GLOBE VALVE

ANGLE | CAST IRON | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7308 - STOP TYPE
JIS F7376 - SDNR TYPE
CONNECTION : JIS 10K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750246	751141	50	120	155	120	4	19	18.2
750247	751142	65	130	175	140	4	19	25.4
750248	751143	80	140	185	150	8	19	27.4
750249	751144	100	160	210	175	8	19	40.6
750250	751145	125	180	250	210	8	23	69.9
750251	751146	150	205	280	240	8	23	81
750252	751147	200	230	330	290	12	23	125
750253	751148	250	290	400	355	12	25	211
750254	751149	300	320	445	400	16	25	293
750255	751150	350	360	490	445	16	25	386
750256	751151	400	420	560	510	16	27	544



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com