

GLOBE VALVE ANGLE | CAST STEEL | JIS 20K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7314 - STOP TYPE
JIS F7474 - SDNR TYPE
CONNECTION : JIS 20K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
750441	751246	32	100	135	100	4	19	13
750442	751247	40	110	140	105	4	19	15.2
750443	751248	50	125	155	120	8	19	20
750444	751249	65	135	175	140	8	19	26.9
750445	751250	80	150	200	160	8	23	38.9
750446	751251	100	170	225	185	8	23	54.4
750447	751252	125	200	270	225	8	25	80.7
750448	751253	150	225	305	260	12	25	112.3
750449	751254	200	280	350	305	12	25	183
750450	751255	250	310	430	380	12	27	285.9



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com