

GATE VALVE CAST STEEL | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7366-5K
CONNECTION : JIS 5K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
750901-5K	50	180	130	105	4	15	13.5
750902-5K	65	190	155	130	4	15	19
750903-5K	80	200	180	145	4	19	24.2
750904-5K	100	230	200	165	8	19	35.3
750905-5K	125	250	235	200	8	19	48.1
750906-5K	150	270	265	230	8	19	65.3
750907-5K	200	290	320	280	8	23	103
750908-5K	250	330	385	345	12	23	164
750909-5K	300	370	430	390	12	23	236
750910-5K	350	410	480	435	12	25	307
750911-5K	400	470	540	495	16	25	405



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com