

GATE VALVE CAST IRON | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7363
CONNECTION : JIS 5K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
750801	50	180	130	105	4	15	13.5
750802	65	190	155	130	4	15	19
750803	80	200	180	145	4	19	24.2
750804	100	230	200	165	8	19	35.3
750805	125	250	235	200	8	19	48.1
750806	150	270	265	230	8	19	65.3
750807	200	290	320	280	8	23	103
750808	250	330	385	345	12	23	164
750809	300	370	430	390	12	23	236
750810	350	410	480	435	12	25	307
750811	400	470	540	495	16	25	405
750812	450	500	605	555	16	25	556
750813	500	550	655	605	20	25	700



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com