

GATE VALVE CAST IRON | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7364
CONNECTION : JIS 10K
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
750821	50	200	155	120	4	19	19.4
750822	65	220	175	140	4	19	27.6
750823	80	230	185	150	8	19	33
750824	100	250	210	175	8	19	45.8
750825	125	270	250	210	8	23	65.9
750826	150	290	280	240	8	23	86
750827	200	320	330	290	12	23	136
750828	250	380	400	355	12	25	230
750829	300	440	445	400	16	25	331
750830	350	500	490	445	16	25	433
750831	400	590	560	510	16	27	597
750832	450	640	620	565	20	27	704
750833	500	710	675	620	20	27	901



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com