

STORM VALVE

VERTICAL

CAST STEEL

JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : BRONZE
DISC : BRONZE
STEM : BRASS

TECHNICAL SPECIFICATION

MODEL : JIS F3060
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
754241-10K	50	210	155	120	4	19	14.7
754242-10K	65	240	175	140	4	19	21.3
754243-10K	80	260	185	150	8	19	37.7
754244-10K	100	280	210	175	8	19	40.8
754245-10K	125	330	250	210	8	23	57.6
754246-10K	150	360	280	240	8	23	80.3
754247-10K	200	500	330	290	12	23	93.4



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com