

STORM VALVE

ANGLE | CAST STEEL | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : BRONZE
DISC : BRONZE
STEM : BRASS

TECHNICAL SPECIFICATION

MODEL : JIS F3060R
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
754251-10K	50	170	155	120	4	19	13
754252-10K	65	200	175	140	4	19	19
754253-10K	80	220	185	150	8	19	23.8
754254-10K	100	250	210	175	8	19	29.6
754255-10K	125	270	250	210	8	23	50
754256-10K	150	310	280	240	8	23	67
754257-10K	200	400	330	290	12	23	96



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com