

GLOBE VALVE

STRAIGHT

CAST IRON

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : ECO. 241 (STOP TYPE)
ECO. 268 (SDNR TYPE)
CONNECTION : DIN PN10
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
755231	755231-NR	15	130	95	65	4	14	4.5
755232	755232-NR	20	150	105	75	4	14	5.5
755233	755233-NR	25	160	115	85	4	14	8.5
755234	755234-NR	32	180	140	100	4	18	9
755235	755235-NR	40	200	150	110	4	18	12.5
755236	755236-NR	50	230	165	125	4	18	15.5
755237	755237-NR	65	290	185	145	4	18	22
755238	755238-NR	80	310	200	160	8	18	27.5
755239	755239-NR	100	350	220	180	8	18	38.5
755240	755240-NR	125	400	250	210	8	18	60
755241	755241-NR	150	480	285	240	8	22	83
755243	755243-NR	200	600	340	295	8	22	127
755244	755244-NR	250	730	395	350	12	22	255
755245	755245-NR	300	850	445	400	12	22	355



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com