

QUICK CLOSING VALVE

STRAIGHT

CAST STEEL

JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7399
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
874503-10K	50	220	155	120	4	19	21.6
874504-10K	65	270	175	140	4	19	31.4
874505-10K	80	300	185	150	8	19	36
874506-10K	100	350	210	175	8	19	57
874507-10K	125	420	250	210	8	23	88.4
874508-10K	150	490	280	240	8	23	115
874509-10K	200	570	330	290	12	23	187.4



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com