

BUTTERFLY VALVE

WAFER

CONCENTRIC

LVR

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION

BODY : GG25
SEAT : NBR
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION


MODEL : 700G-1T
CONNECTION : JIS 5K & JIS 10K & DIN PN10 & DIN PN16
ACTUATION : LOCK LEVER
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER
C : PCD
NO : NUMBER OF HOLES
H2 : DIAMETER OF HOLES
H : SHAFT
T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

						TOP FLANGE					
CODE	DN	L	NO	h	W	d	c	no	h2	H	T-FLG
752208	40	35	2	19	2.1	90	70	4	9	9	F07
752201	50	43	2	19	2.4	90	70	4	9	9	F07
752202	65	46	2	19	2.8	90	70	4	9	9	F07
752203	80	46	4	19	3.4	90	70	4	9	9	F07
752204	100	52	4	19	4.4	90	70	4	9	11	F07
752205	125	56	4	19	5.8	90	70	4	9	14	F07
752206	150	56	4	23	7	90	70	4	9	14	F07
752207	200	280	8	23	132.2	125	102	4	12	17	F10



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com