

QUICK CLOSING VALVE

ANGLE

CAST STEEL

JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7399
CONNECTION : JIS 5K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
874523	50	100	130	105	4	15	16
874524	65	115	155	130	4	15	23
874525	80	130	180	145	4	19	28.2
874526	100	150	200	165	8	19	45.6
874527	125	170	235	200	8	19	61.4
874528	150	190	265	230	8	19	83.2
874529	200	220	320	280	8	23	132.2



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com