

QUICK CLOSING VALVE

ANGLE | CAST STEEL | JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : JIS F7399
CONNECTION : JIS 10K
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
874523-10K	50	120	155	120	4	19	20.4
874524-10K	65	130	175	140	4	19	27.8
874525-10K	80	140	185	150	8	19	30
874526-10K	100	160	210	175	8	19	50
874527-10K	125	180	250	210	8	23	72.2
874528-10K	150	205	280	240	8	23	94.6
874529-10K	200	230	330	290	12	23	139.5



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com