

BUTTERFLY VALVE

WAFER

CONCENTRIC

GRB

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION

BODY : GG25
SEAT : NBR
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION


MODEL : 700G-2U
CONNECTION : JIS 5K & JIS 10K & DIN PN10 & DIN PN16
ACTUATION : WORM GEAR ACTUATOR
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER
C : PCD
NO : NUMBER OF HOLES
H2 : DIAMETER OF HOLES
H : SHAFT
T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

						TOP FLANGE					
CODE	DN	L	NO	h	W	d	c	no	h2	H	T-FLG
752227	40	35	2	19	3.8	90	70	4	9	9	F07
752211	50	43	2	19	4.1	90	70	4	9	9	F07
752212	65	46	2	19	4.8	90	70	4	9	9	F07
752213	80	46	4	19	4.9	90	70	4	9	9	F07
752214	100	52	4	19	5.7	90	70	4	9	11	F07
752215	125	56	4	19	9.6	90	70	4	9	14	F07
752216	150	56	4	23	11.2	90	70	4	9	14	F07
752217	200	60	4	23	18	125	102	4	12	17	F10
752218	250	68	4	25	26	125	102	4	12	22	F10
752219	300	78	4	25	39	150	125	4	14	22	F12
752220	350	78	4	25	58	150	125	4	14	22	F12
752221	400	102	4	27	80	150	125	4	14	27	F12
752222	450	114	4	27	103	210	165	4	22	27	F16
752223	500	127	4	27	130	210	165	4	22	36	F16
752224	550	154	4	33	199	210	165	4	22	36	F16
752225	600	154	4	33	222	210	165	4	22	36	F16
752261	650	165	4	33	350	300	254	8	18		F25
752262	700	165	4	33	410	300	254	8	18		F25



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com