

BUTTERFLY VALVE

LUG | CONCENTRIC | GRB | JIS 5K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GG-25 & GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : 704G-2U

CONNECTION : JIS 5K

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : 3.1 MILL DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

							TOP FLANGE					
CODE	DN	L	C	NO	h	W	d	c	no	h2	H	T-FLG
752311	40	35	95	4	M12	2.25	90	70	4	9	9	F07
752312	50	43	105	4	M16	3.9	90	70	4	9	9	F07
752313	65	46	130	4	M16	4.23	90	70	4	9	9	F07
752314	80	46	145	4	M16	5.78	90	70	4	9	9	F07
752315	100	52	165	8	M16	7.53	90	70	4	9	11	F07
752316	125	56	200	8	M16	10.16	90	70	4	9	14	F07
752317	150	56	230	8	M16	12.3	90	70	4	9	14	F07
752318	200	60	280	8	M20	20.86	125	102	4	12	17	F10
752319	250	68	345	12	M20	31.5	125	102	4	12	22	F10
752320	300	78	390	12	M20	49	150	125	4	14	22	F12
7523350	350	78	435	12	M22	72.4	150	125	4	14	22	F12
7523400	400	102	495	16	M22	98.7	150	125	4	14	27	F12
7523450	450	114	555	16	M22	127.6	210	165	4	22	27	F16



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com