

BUTTERFLY VALVE

SEMI LUG

CONCENTRIC

GRB

JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION

BODY : GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : 705G-2U

CONNECTION : JIS 10K

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

							TOP FLANGE					
CODE	DN	L	C	NO	h	W	d	c	no	h2	H	T-FLG
752265	50	43	120	4	M16	4.8	90	70	4	9	9	F07
752266	65	46	140	4	M16	5.8	90	70	4	9	9	F07
752267	80	46	150	4	M16	6.3	90	70	4	9	9	F07
752268	100	52	175	4	M16	7.3	90	70	4	9	11	F07
752269	125	56	210	4	M16	12.2	90	70	4	9	14	F07
752270	150	56	240	4	M20	16	90	70	4	9	14	F07
752271	200	60	290	4	M20	23	125	102	4	12	17	F10
752272	250	68	355	4	M22	32	125	102	4	12	22	F10
752273	300	78	400	4	M22	45	150	125	4	14	22	F12
752274	350	78	445	4	M22	63	150	125	4	14	22	F12
752275	400	102	510	4	M24	91	150	125	4	14	27	F12
752276	450	114	565	4	M24	115	210	165	4	22	27	F16
752277	500	127	620	4	M24	145	210	165	4	22	36	F16
752278	550	154	680	4	M30	199	210	165	4	22	36	F16
752279	600	154	730	4	M30	225	210	165	4	22	36	F16
752280	650	165	780	4	M30	350	300	254	8	18		F25
752281	700	165	840	4	M30	410	300	254	8	18		F25



VALVE TURKIYE

+90 232 616 17 19

valves@adamarine.com

VALVE EUROPE

+31 180 22 4000

valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553

valves.ch@adamarine.com

www.marinevalves.com