

BUTTERFLY VALVE

LUG

CONCENTRIC

LVR

JIS 10K

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GG-25 & GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : 704G-1T

CONNECTION : JIS 10K

ACTUATION : LOCK LEVER

CERTIFICATION : 3.1 MILL DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

							TOP FLANGE					
CODE	DN	L	C	NO	h	W	d	c	no	h2	H	T-FLG
752321	40	35	105	4	M16	2.25	90	70	4	9	9	F07
752322	50	43	120	4	M16	3.9	90	70	4	9	9	F07
752323	65	46	140	4	M16	4.23	90	70	4	9	9	F07
752324	80	46	150	8	M16	5.78	90	70	4	9	9	F07
752325	100	52	175	8	M16	7.53	90	70	4	9	11	F07
752326	125	56	210	8	M20	10.16	90	70	4	9	14	F07



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com