

BUTTERFLY VALVE

FLANGED SHORT

CONCENTRIC

GRB

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : 722F-2U-SHORT

CONNECTION : JIS 10K & DIN PN10 & DIN PN16

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

CODE	DN	L	C	NO	h	W	TOP FLANGE					
							d	c	no	h2	H	T-FLG
752340	100	52		UNDRILLED		11	90	70	4	9	11	F07
752341	125	56		UNDRILLED		13	90	70	4	9	14	F07
752342	150	56		UNDRILLED		19	90	70	4	9	14	F07
752343	200	60		UNDRILLED		25.8	125	102	4	12	17	F10
752344	250	68		UNDRILLED		34.8	125	102	4	12	22	F10
752345	300	78		UNDRILLED		56.5	150	125	4	14	22	F12
752346	350	78		UNDRILLED		69.8	150	125	4	14	22	F12
752347	400	102		UNDRILLED		128	150	125	4	14	27	F12
752348	450	114		UNDRILLED		152	210	165	4	22	27	F16
752349	500	127		UNDRILLED		181	210	165	4	22	36	F16
7523550	550	154		UNDRILLED		238	210	165	4	22	36	F16
752350	600	154		UNDRILLED		292.6	210	165	4	22	36	F16
7523650	650	165		UNDRILLED		345	300	254	8	18		F25
752351	700	165		UNDRILLED		377	300	254	8	18		F25



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com