

BUTTERFLY VALVE

FLANGED

DOUBLE ECCENTRIC

HFR

APPLICATION

High-Performance Flange type Rubber Seat Butterfly Valves are without drill. Can be drilled as above flange connections.

MATERIAL SPECIFICATION

BODY : A216 WCB

DISC : A351 CF8


STEM : A256 T410

SEAT : VITON

TECHNICAL SPECIFICATION

MODEL : HFR

CONNECTION : JIS 10K & JIS 16K & JIS 20K & DIN PN16 & DIN PN25 & DIN PN40



DIMENSION TABLE

SIZE		d	L	H	H1	H2	H3	STEM				TOP FLANGE				WEIGHT (KG)
INCH	MM							D	KEY SIZE	SQUARE		TYPE	N	M	N-Z	
										SQ	H4					
2"	50	50	108	331	118	168	45	16	5x5	12	33	F07	70	90	4-9	14
2.5"	65	65	112	355	133	177	45	16	5x5	12	33	F07	70	90	4-9	18
3"	80	80	114	374	144	185	45	19	6x6	12	33	F07	70	90	4-9	22
4"	100	100	127	409	164	200	45	19	6x6	12	33	F07	70	90	4-9	28
5"	125	125	140	450	188	217	45	19	6x6	12	33	F07	70	90	4-9	37
6"	150	150	140	490	205	240	45	19	6x6	12	33	F07	70	90	4-9	44
8"	200	200	152	553	223	270	60	25	8x7	17	55	F10	102	125	4-12	64
10"	250	250	165	655	275	320	60	25	8x7	22	55	F10	102	125	4-12	87
12"	300	300	178	718	308	350	60	32	10x8	27	55	F10	102	125	4-12	123



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com