

GLOBE VALVE ANGLE | CAST IRON | DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GG-25
BONNET : GG-25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : ECO. 242 (STOP TYPE)
ECO. 269 (SDNR TYPE)
CONNECTION : DIN PN10
CERTIFICATION : 3.1 MILL CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
755246	755246-NR	15	90	95	65	4	14	4
755247	755247-NR	20	95	105	75	4	14	4.5
755248	755248-NR	25	100	115	85	4	14	5.6
755249	755249-NR	32	105	140	100	4	18	6.6
755250	755250-NR	40	115	150	110	4	18	9.2
755251	755251-NR	50	125	165	125	4	18	11.6
755252	755252-NR	65	145	185	145	4	18	17
755253	755253-NR	80	155	200	160	8	18	22.6
755254	755254-NR	100	175	220	180	8	18	33
755255	755255-NR	125	200	250	210	8	18	46
755256	755256-NR	150	225	285	240	8	22	68
755258	755258-NR	200	275	340	295	8	22	100
755259	755259-NR	250	325	395	350	12	22	204
755260	755260-NR	300	375	445	400	12	22	260



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com