

GLOBE VALVE

STRAIGHT | CAST STEEL | DIN PN40

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : ECO. 417 (STOP TYPE)
ECO. 417-NR (SDNR TYPE)
CONNECTION : DIN PN40
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE STOP	CODE SDNR	DN	L	D	C	NO	h	W
755326	755326-NR	15	130	95	65	4	14	4.8
755327	755327-NR	20	150	105	75	4	14	5.4
755328	755328-NR	25	160	115	85	4	14	7.1
755329	755329-NR	32	180	140	100	4	18	8
755330	755330-NR	40	200	150	110	4	18	11.5
755331	755331-NR	50	230	165	125	4	18	13.5
755332	755332-NR	65	290	185	145	8	18	23.5
755333	755333-NR	80	310	200	160	8	18	28
755334	755334-NR	100	350	235	190	8	22	40
755335	755335-NR	125	400	270	220	8	26	61
755336	755336-NR	150	480	300	250	8	26	84
755338	755338-NR	200	600	375	320	12	30	170
755339	755339-NR	250	730	450	385	12	33	283
755340	755340-NR	300	850	515	450	16	33	414



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com