

GATE VALVE

NODULAR CAST IRON

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GGG40.3
BONNET : GGG40.3
SEAT : BRONZE
DISC : BRONZE
STEM : BRASS

TECHNICAL SPECIFICATION

MODEL : ECO 317KL
CONNECTION : DIN PN10
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
755661	40	140	150	110	4	18	11
755662	50	150	165	125	4	18	13
755663	65	170	185	145	4	18	17
755664	80	180	200	160	8	18	20
755665	100	190	220	180	8	18	28
755666	125	200	250	210	8	18	40
755667	150	210	285	240	8	22	50
755668	200	230	340	295	8	22	63
755669	250	250	395	350	12	22	80
755670	300	270	445	400	12	22	130
755671	350	290	505	460	16	22	170
755672	400	310	565	515	16	26	230



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com