

STORM VALVE

ANGLE

CAST STEEL

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GS-C25
BONNET : GS-C25
SEAT : BRONZE
DISC : BRONZE
STEM : BRASS

TECHNICAL SPECIFICATION

MODEL : ECO. 1207
CONNECTION : DIN PN10
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
754277	50	180	165	125	4	18	12
754278	65	200	185	145	4	18	14
754279	80	215	200	160	8	18	18
754280	100	250	220	180	8	18	27
754281	125	290	250	210	8	18	37
754282	150	330	285	240	8	22	49



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com