

BUTTERFLY VALVE

FLANGED

CONCENTRIC

GRB

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : SERIES 53

CONNECTION : DIN PN10

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

							TOP FLANGE					
CODE	DN	L	C	NO	h	W	d	c	no	h2	H	T-FLG
754581-G	50	108	125	4	18	4.1	90	70	4	9	9	F07
754582-G	65	112	145	4	18	5.5	90	70	4	9	9	F07
754583-G	80	114	160	8	18	6.8	90	70	4	9	9	F07
754584-G	100	127	180	8	18	8.6	90	70	4	9	11	F07
754585-G	125	140	210	8	18	10.5	90	70	4	9	14	F07
754586-G	150	140	240	8	22	12.5	90	70	4	9	14	F07
754587	200	152	295	8	22	21.4	125	102	4	12	17	F10
754588	250	165	350	12	22	29.3	125	102	4	12	22	F10
754589	300	178	400	12	22	44	150	125	4	14	22	F12
754590	350	190	460	16	22	62.2	150	125	4	14	22	F12
754591	400	216	515	16	26	112	150	125	4	14	27	F12
754592	450	222	565	20	26	153	210	165	4	22	27	F16
754593	500	229	620	20	26	150	210	165	4	22	36	F16
754594	600	267	725	20	30	200	210	165	4	22	36	F16



VALVE TURKIYE

+90 232 616 17 19

valves@adamarine.com

VALVE EUROPE

+31 180 22 4000

valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553

valves.ch@adamarine.com

www.marinevalves.com