

QUICK CLOSING VALVE

STRAIGHT

DUCTILE IRON

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION


BODY : GGG40
BONNET : GGG40
SEAT : SUS316
DISC : SUS316
STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : ECO. 100/247HP
CONNECTION : DIN PN10
CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE
D : F.O.D
C : P.C.D
NO : NUMBER OF HOLES
H : DIAMETER OF HOLES
W : WEIGHT



DIMENSION TABLE

CODE	DN	L	D	C	NO	h	W
874621	15	130	95	65	4	14	5.0
874622	20	150	105	75	4	14	6.0
874623	25	160	115	85	4	14	6.5
874624	32	180	140	100	4	18	9.5
874625	40	200	150	110	4	18	12.5
874626	50	230	165	125	4	18	17
874627	65	290	185	145	4	18	28
874628	80	310	200	160	8	18	31
874629	100	350	220	180	8	18	45
874630	125	400	250	210	8	18	66
874645	150	480	285	240	8	22	74.5



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com