

BUTTERFLY VALVE

LUG

CONCENTRIC

GRB

DIN PN10

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GG-25 & GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : SERIES 52

CONNECTION : DIN PN10

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : 3.1 MILL, DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

CODE	DN	L	C	NO	h	W	TOP FLANGE					
							d	c	no	h2	H	T-FLG
754431-G	50	43	125	4	M16	4.1	90	70	4	9	9	F07
754432-G	65	46	145	4	M16	5.5	90	70	4	9	9	F07
754433-G	80	46	160	8	M16	6.8	90	70	4	9	9	F07
754434-G	100	52	180	8	M16	8.6	90	70	4	9	11	F07
754435-G	125	56	210	8	M16	10.5	90	70	4	9	14	F07
754436-G	150	56	240	8	M20	12.5	90	70	4	9	14	F07
754437	200	60	295	8	M20	21.4	125	102	4	12	17	F10
754438	250	68	350	12	M20	29.3	125	102	4	12	22	F10
754439	300	78	400	12	M20	44	150	125	4	14	22	F12
754440	350	78	460	16	M20	62.2	150	125	4	14	22	F12
754441	400	114	515	16	M22	112	150	125	4	14	27	F12
754442	450	127	565	20	M22	153	210	165	4	22	27	F16



VALVE TURKIYE

+90 232 616 17 19

valves@adamarine.com

VALVE EUROPE

+31 180 22 4000

valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553

valves.ch@adamarine.com

www.marinevalves.com