

BUTTERFLY VALVE

LUG

CONCENTRIC

GRB

DIN PN16

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil and steam.

MATERIAL SPECIFICATION

BODY : GG-25 & GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : SERIES 52

CONNECTION : DIN PN16

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : 3.1 MILL, DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

							TOP FLANGE					
CODE	DN	L	C	NO	h	W	d	c	no	h2	H	T-FLG
754446	50	43	125	4	M16	4.1	90	70	4	9	9	F07
754447	65	46	145	4	M16	5.5	90	70	4	9	9	F07
754448	80	46	160	8	M16	6.8	90	70	4	9	9	F07
754449	100	52	180	8	M16	8.6	90	70	4	9	11	F07
754450	125	56	210	8	M16	10.5	90	70	4	9	14	F07
754451	150	56	240	8	M20	12.5	90	70	4	9	14	F07
754452	200	60	295	12	M20	21.4	125	102	4	12	17	F10
754453	250	68	355	12	M24	29.3	125	102	4	12	22	F10
754454	300	78	410	12	M24	44	150	125	4	14	22	F12
754455	350	78	470	16	M24	62.2	150	125	4	14	22	F12
754456	400	114	525	16	M27	112	150	125	4	14	27	F12
754457	450	127	585	20	M27	153	210	165	4	22	27	F16



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com