

BUTTERFLY VALVE

FLANGED

CONCENTRIC

GRB

DIN PN16

APPLICATION

Aboard ships for hot and cold water, fresh water, sea water, oil, and steam.

MATERIAL SPECIFICATION

BODY : GGG.40

SEAT : NBR

DISC : ALBC

STEM : SUS316

TECHNICAL SPECIFICATION

MODEL : SERIES 53

CONNECTION : DIN PN16

ACTUATION : WORM GEAR ACTUATOR

CERTIFICATION : DNV-GL CLASS CERTIFICATE

DIMENSIONS SPECIFICATION

L : FACE TO FACE

C : P.C.D

NO : NUMBER OF HOLES

H : DIAMETER OF HOLES

W : WEIGHT

TOP FLANGE

D : OUTSIDE DIAMETER


C : PCD

NO : NUMBER OF HOLES

H2 : DIAMETER OF HOLES

H : SHAFT

T-FLG : TOP FLANGE STANDARD



DIMENSION TABLE

CODE	DN	L	C	NO	h	W	TOP FLANGE					
							d	c	no	h2	H	T-FLG
754601	50	108	125	4	18	4.1	90	70	4	9	9	F07
754602	65	112	145	4	18	5.5	90	70	4	9	9	F07
754603	80	114	160	8	18	6.8	90	70	4	9	9	F07
754604	100	127	180	8	18	8.6	90	70	4	9	11	F07
754605	125	140	210	8	18	10.5	90	70	4	9	14	F07
754606	150	140	240	8	22	12.5	90	70	4	9	14	F07
754607	200	152	295	12	22	21.4	125	102	4	12	17	F10
754608	250	165	355	12	26	29.3	125	102	4	12	22	F10
754609	300	178	410	12	26	44	150	125	4	14	22	F12
754610	350	190	470	16	26	62.2	150	125	4	14	22	F12
754611	400	216	525	16	30	112	150	125	4	14	27	F12
754612	450	222	585	20	30	153	210	165	4	22	27	F16
754613	500	229	650	20	33	150	210	165	4	22	36	F16
754614	600	267	770	20	36	200	210	165	4	22	36	F16



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com