

BUTTERFLY VALVE

WAFER

DOUBLE ECCENTRIC

HWR

APPLICATION

High-Performance Wafer type Rubber Seat Butterfly Valves are without drill. Can be drilled as above flange connections.

MATERIAL SPECIFICATION

BODY : A216 WCB

DISC : A351 CF8


STEM : A256 T410

SEAT : VITON

TECHNICAL SPECIFICATION

MODEL : HWR

CONNECTION : JIS 10K & JIS 16K & JIS 20K & DIN PN16 & DIN PN25 & DIN PN40



DIMENSION TABLE

SIZE		d	L	H	H1	H2	H3	STEM				TOP FLANGE				WEIGHT (KG)
INCH	MM							D	KEY SIZE	SQUARE		TYPE	N	M	N-Z	
										SQ	H4					
2"	50	50	43	331	118	168	45	16	5x5	12	33	F07	70	90	4-9	4.5
2.5"	65	65	46	355	133	177	45	16	5x5	12	33	F07	70	90	4-9	5.5
3"	80	80	48	374	144	185	45	19	6x6	12	33	F07	70	90	4-9	9.0
4"	100	100	54	409	164	200	45	19	6x6	12	33	F07	70	90	4-9	10.0
5"	125	125	57	450	188	217	45	19	6x6	12	33	F07	70	90	4-9	13.0
6"	150	150	57	490	205	240	45	19	6x6	12	33	F07	70	90	4-9	17.0
8"	200	200	64	553	223	270	60	25	8x7	17	55	F10	102	125	4-12	26.0
10"	250	250	71	655	275	320	60	25	8x7	22	55	F10	102	125	4-12	40.0



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com