

BUTTERFLY VALVE SEMI LUG | DOUBLE ECCENTRIC | HSP-A74S

APPLICATION

High-Performance Semi-Lug type Teflon Seat Butterfly Valves are without drill. Can be drilled as above flange connections.

MATERIAL SPECIFICATION

BODY : A351 CF8

DISC : A351 CF8


STEM : 17-4PHSS

SEAT : P287

TECHNICAL SPECIFICATION

MODEL : HSP-A74S

CONNECTION : JIS 10K & JIS 16K & JIS 20K & DIN PN16 & DIN PN25 & DIN PN40



DIMENSION TABLE

SIZE		d	L	H	H1	H2	H3	STEM				TOP FLANGE				WEIGHT (KG)
INCH	MM							D	KEY SIZE	SQUARE		TYPE	N	M	N-Z	
										SQ	H4					
2"	50	50	43	218,5	79	126	13,5	X	X	11	13,5	F05	50	70	4-9	5
2.5"	65	65	46	226,5	87	126	13,5	X	X	11	13,5	F05	50	70	4-9	6
3"	80	80	48	262,5	100	145	17,5	X	X	11	17,5	F07	70	90	4-9	8
4"	100	100	54	311,5	124	170	17,5	X	X	14	17,5	F07	70	90	4-9	10
5"	125	125	57	346,5	144	185	17,5	X	X	14	17,5	F07	70	90	4-9	15
6"	150	150	57	371,5	150	203	18,5	X	X	17	18,5	F10	102	125	4-12	20
8"	200	200	64	449,5	186	239	24,5	X	X	22	24,5	F10	102	125	4-12	23
10"	250	250	71	539,5	240	275	24,5	X	X	27	24,5	F10	102	125	4-12	42
12"	300	300	81	588	251	307	30	X	X	27	30	F12	125	140	4-12	60
14"	350	350	91	661	294	337	30	X	X	36	30	F12	125	140	4-12	100
16"	400	400	102	730	332	368	30	X	X	46	30	F14	140	175	4-18	155



VALVE TURKIYE

+90 232 616 17 19
valves@adamarine.com

VALVE EUROPE

+31 180 22 4000
valves.nl@adamarine.com

VALVE ASIA

+86 186 2606 6553
valves.ch@adamarine.com

www.marinevalves.com